Office of Naval Research

Contract N00014-67-A-0298-0006

NR - 372 - 012

National Aeronautics and Space Administration

Grant NGR-22-007-068

CONJUGATE GRADIENT METHODS WITH AN APPLICATION TO V/STOL FLIGHT-PATH OPTIMIZATION

By

R. K. Mehra and A. E. Bryson, Jr.

Technical Report No. 543

November 1967

Division of Engineering and Applied Physics

Harvard University Cambridge, Massachusetts

CONJUGATE GRADIENT METHODS WITH AN APPLICATION TO V/STOL FLIGHT-PATH OPTIMIZATION

By

R. K. Mehra and A. E. Bryson, Jr.

Division of Engineering and Applied Physics

Harvard University   Cambridge, Massachusetts

ABSTRACT

Conjugate gradient methods have recently been applied to some simple optimization problems and have been shown to converge faster than the methods of steepest descent. The present paper considers application of these methods to more complicated problems involving terminal as well as in-flight constraints. A number of methods are suggested to handle these constraints and the numerical difficulties associated with each method are discussed. The problem of flight-path optimization of a V/STOL aircraft has been considered and minimum time paths for the climb phase have been obtained using the conjugate gradient algorithm. In conclusion, some remarks are made about the relative efficiency of the different optimization schemes presently available for the solution of optimal control problems.

I. Introduction

Hestenes and Stiefel (1) in 1952 introduced the method of con-
jugate gradients for solving linear sets of equations. The same method
was used by Fletcher and Reeves (2) in 1964 to solve nonlinear pro-
gramming problems. Hayes (3) extended the method in 1954 to the
solution of linear problems on Hilbert spaces. Antosiewicz and
Rheinboldt (4) derived in 1962 convergence rates for these problems
and showed that convergence is obtained in a finite number of steps for
the linear-quadra c problem. Improved estimates of rates of con-
vergence were obtained by Daniel (5) in 1965. Lasdon, Mitter and
Warren (6) applied this method in 1966 to the solution of optimal
control problems. They showed that the conjugate gradient method
converged faster than the steepest-descent method on a number of
problems. Sinnott and Luenberger (7) recently used another variant
of the conjugate gradient method and gave similar results. In
addition, they extended the method to handle linear terminal con-
straints.

Most of the optimal control problems solved so far (6, 7) using
conjugate gradient methods have been simple in structure involving
either no or very few terminal constraints. Lasdon, Warren and
Rice (8) have tried using an extension of the Fiacco-McCormick
"Sequential Unconstrained Minimization Technique" to handle in-
flight inequality constraints, but the results were not too satisfactory
for the problem of range-maximization of a re-entry vehicle. (This
problem was originally solved by Bryson and Denham (9) using the
method of steepest-descent). Speyer, Mehra and Bryson (10) solved

the same problem using a separation technique to handle the state-variable inequality constraint. This separation method has been described in detail in reference 10. It will be briefly outlined in section IV along with other methods for handling in-flight constraints. Some of these methods will then be applied in section V to the flight path optimization of a V/STOL aircraft.

II. Conjugate Gradient Methods

a) <u>Parameter Optimization</u>: Conjugate gradient methods have the property that they minimize a quadratic function of n variables in n or less number of steps. They do so by generating a set of n directions known as conjugate directions which span the n-dimensional space. Let the function to be minimized be $J = \frac{1}{2}(x - h)^T A(x - h)$ and let $p_0, p_1, \ldots, p_{n-1}$ be n vectors in Euclidean n space. They will be called "A-orthogonal" or "A-conjugate", iff

$$p_i^T A p_j = 0 , \qquad i \neq j \tag{1}$$

where A is a positive definite matrix.

Therefore,

$$p_i^T A p_i > 0 , \qquad \text{if } p_i \neq 0 \tag{2}$$

It is easy to show that n "A-conjugate" vectors are linearly independent and form a basis for the n-dimensional space. If x_0 is the initial guess, then $(h - x_0)$ can be expressed in terms of this basis as follows:

$$h - x_0 = \sum_{i=0}^{n-1} a_i p_i \tag{3}$$

$$\text{where } a_i = \frac{-p_i^T A(x_0 - h)}{p_i^T A p_i} = \frac{-p_i^T g_0}{p_i^T A p_i} \tag{4}$$

-2-

where $g_o = A(x_o - h)$ is the gradient vector $\left. \frac{\partial J}{\partial x} \right|_{x=x_o}$.

All conjugate gradient methods generate conjugate directions in one or another way. Basically conjugate directions p_i can be generated by a Gram-Schmidt orthogonalization procedure starting from any arbitrary set $v_o, v_1, \ldots, v_{n-1}$ of vectors. It can be shown that if v_i are the coordinate vectors, then the conjugate gradient method is functionally equivalent to the gaussian elimination procedure. But the most convenient choice for v_i is the negative gradient vectors or the residue vectors r_i:

$$r_i = -g_i = A(h - x_i) \tag{5}$$

This choice leads to a number of simplifications and, finally the following algorithm is obtained. Details of the proof can be found in Beckman (20).

$$x_o \quad \text{arbitrary}$$

$$g_o = g(x_o)$$

$$p_o = -g_o$$

$$x_{i+1} = x_i + a_i p_i \qquad \text{where} \quad a_i = \frac{-p_i^T g_i}{p_i^T A p_i} \tag{6}$$

$$p_{i+1} = -g_{i+1} + \beta_i p_i \qquad \text{where} \quad \beta_i = \frac{\| g_{i+1} \|^2}{\| g_i \|^2} \tag{7}$$

This algorithm can be used for nonlinear programming problems as well. However, the matrix A is no longer a constant matrix and has to be computed at each step. One can avoid this by noting that if J is minimized along the direction $(x_i + c_i p_i)$ with respect to c_i, the optimum value of c_i is exactly a_i (20). Notice that if $\beta_i = 0$, the conjugate gradient method becomes a steepest descent method.

The conjugate gradient algorithm has a number of interesting properties. Rutishauser (11) compares it with other gradient methods and shows that it is the best method amongst a class of iterative gradient procedures for solving linear sets of equations. If ϵ_i denotes the error vector $(h - x_i)$, it can be shown that $\| \epsilon_{i+1} \| < \| \epsilon_i \| \forall i$. Also, it can be shown that J is decreased at each step. Geometrically, p_i is the projection of the negative gradient vector g_i on to the subspace spanned by $p_i, p_{i+1}, \cdots, p_{n-1}$. Thus we successively reduce the dimension of the subspace onto which $-g_i$ is projected. This gives convergence in a finite number of steps.

b) <u>Optimal Control Problems</u>: Conjugate gradient methods can be readily extended to Hilbert spaces (3, 5). Consider the Mayer problem in the Calculus of Variations: Find u(t) to

$$\text{minimize} \quad J = \phi(x(t_f))$$

$$\text{subject to} \quad \dot{x} = f(x, u, t). \qquad (8)$$

$x(t_o)$ and t_f are given, but $x(t_f)$ is free.

x is an n x 1 state vector and u is an r x 1 control vector, both functions of time variable t.

The Hamiltonian of the system is $H = \lambda^T f$,   (9)

and the adjoint equations are $\dot{\lambda} = -f_x^T \lambda$ (10)

$$\lambda(t_f) = \phi_x(x(t_f), t_f) \qquad (11)$$

Let $g(t) = \dfrac{\partial H}{\partial u} = \lambda^T \dfrac{\partial f}{\partial u}$ (12)

g is a vector of functions and relates δJ to δu (13, chapter II).

$$\delta J = \int_{t_o}^{t_f} g\,\delta u\, dt \qquad (13)$$

g plays the role of gradient vector in the finite dimensional case.

The same algorithm (equations 6 and 7) applies except that the scalar multiplications are changed to integrations. E.g., $\|g_i\|^2 = \int_{t_o}^{t_f} g_i^T g_i\, dt$.

c) <u>Computation Details</u>: A fourth order Runga-Kutta scheme is used to integrate the Euler-Lagrange Equations. It is necessary to store a direction of search to calculate the next direction of search. A cubic interpolation scheme (2) is used for one-dimensional search. It uses all the information available, i.e., $J(u_i)$, $J(u_{i+1})$, $\dfrac{\partial J(u_i)}{\partial a_i}$, $\dfrac{\partial J(u_{i+1})}{\partial a_i}$ to fit the "smoothest curve" through the points u_i and u_{i+1}, i.e., the curve which minimizes the integral $\int_0^{a_i} \dfrac{d^2 J}{d\sigma^2}\, d\sigma$ where a_i is the step size.

III. Terminal Constraints

The conjugate gradient algorithm as given above applies only to unconstrained minimization problems. Modifications to the algorithm are necessary when there are constraints on the problem. A fairly general optimization problem with terminal constraints can be stated as follows: Find $u(t)$ to

$$\text{minimize} \quad J = \phi(x(t_f), t_f) \qquad (14)$$

$$\text{subject to} \quad \dot{x} = f(x, u, t) \; ; \quad x(t_o) \text{ given} \qquad (15)$$

and $\quad \psi(x(t_f), t_f) = 0 \qquad$ q terminal constraints $\qquad$ (16)

$\quad \Omega(x(t_f), t_f) = 0 \qquad$ stopping condition for $\qquad$ (17)
determining t_f.

In effect, there are (q + 1) terminal constraints. Any one of these can be chosen as a stopping condition. This is an unnecessary, arbitrary but useful device.

Two of the numerical methods for solving such problems are given below.

a) <u>Penalty Function Method</u>: Objective function J is modified using a quadratic penalty function

$$\bar{J} = J + \psi^T K \psi \qquad (18)$$

where K is a positive-definite matrix of penalty function constants. A sequence of unconstrained $\bar{J}$ problems is solved with increasing values of K. In the limit as $K \longrightarrow \infty$ we get $\psi \longrightarrow 0$, $J \longrightarrow J_{opt}$, $u \longrightarrow u_{opt}$. To check the efficiency of this method, it was used to solve a number of problems. The method worked quite well on linear-quadratic problems and simple nonlinear problems. Examples 1 and 2 of Ref. (6) were solved in one computer run by using a large enough value of K. The minimum time earth-to-mars orbit transfer problem of Ref. (12) converged in 18 iterations starting from a stepped nominal and using about 1 minute of IBM 7094 computer time.

However, when this method was tried on flight path optimization problems involving aerodynamic drag and lift terms, the method ran into difficulties whenever the number of terminal constraints was increased beyond two. The reason seems to be that the "frozen-point" eigen-values of

the linearized system are split far apart due to damping terms. We define more clearly what we mean by eigen-values of a nonlinear system: If we linearize the equations around some nominal path and assume that the coefficients of the linearized equations vary sufficiently slowly in time that they may be considered constant over some period of time, we may talk about the eigen-values of this system. For a typical problem involving three state variables, V (velocity), h (altitude) and γ (flight path angle), the convergence was extremely slow if terminal constraints were put on all the three state variables simultaneously. Since for most of these problems, the terminal time is not specified, some sort of stopping condition is needed to determine t_f at each iteration. In this way, one of the constraints is automatically satisfied. It was found that the penalty function method could be used to handle at most two terminal constraints. If there were more terminal constraints, the convergence was extremely slow.

Various other types of penalty functions can be used. However, there is one common difficulty, viz., addition of penalty functions may change the problem completely creating narrow valleys and splitting the eigen-values of the system far apart. An example of this type of behavior is given in (13, chapter I). It is well-known that gradient procedures converge very slowly when the eigen-values of the system are split far apart.

b) Gradient Projection Method: Rosen's gradient projection method (14) was used by Bryson and Denham (9) to solve optimal control problems using a steepest descent method. The same method can be used with the conjugate gradient method to handle linear terminal

constraints (7). If the step size α_i is small so that linearization is valid, the same method should work for nonlinear constraints as well.[*]

Bryson and Denham [9] have derived an expression for the projected gradient, $\overline{g}$. They show that

$$\overline{g} = f_u^T(\lambda_\phi - \lambda_\psi I_{\psi\psi}^{-1} I_{\psi\phi}) \tag{19}$$

where

$$\dot{\lambda}_\phi = -f_x^T \lambda_\phi \ ; \quad \lambda_\phi(t_f) = \phi_x^T(x(t_f), t_f) \tag{20}$$

$$\dot{\lambda}_\psi = -f_x^T \lambda_\psi \ ; \quad \lambda_\psi(t_f) = \psi_x^T(x(t_f), t_f) \tag{21}$$

$$I_{\psi\psi} = \int_{t_o}^{t_f} \lambda_\psi^T f_u f_u^T \lambda_\psi \, dt \tag{22}$$

$$I_{\psi\phi} = \int_{t_o}^{t_f} \lambda_\psi^T f_u f_u^T \lambda_\phi \, dt \tag{23}$$

Conjugate directions $\overline{p}_i$ are generated using $\overline{g}_i$, $\overline{p}_{i-1}$ and equations (6) and (7). If a change $d\psi$ is desired in the constraint level, ψ, the control change δu is given by

$$\delta u = f_u^T \lambda_\psi I_{\psi\psi}^{-1} \, d\psi \quad . \tag{24}$$

The conjugate gradient algorithm is modified as follows:

$$\overline{u}_{i+1} = u_i + m_i \alpha_i \overline{p}_i \tag{25}$$

(i) Start with $m_i = 1$ and obtain α_i by a one-dimensional search.

(ii) Calculate the value of $\overline{\psi}_{i+1}(t_f)$ using $\overline{u}_{i+1}$. If linearization holds, $\overline{\psi}_{i+1}(t_f)$ should be the same as $\psi_i(t_f)$. If not, reduce m_i so that $\|\overline{\psi}_{i+1} - \psi_i\| < \epsilon$, where ϵ is a small positive number.

---

[*] Authors do not have computational experience with this method so far.

(iii) Choose $d\psi_i$ and calculate the corresponding δu_i. Add this to $\overline{u}_{i+1}$

$$u_{i+1} = \overline{u}_{i+1} + \delta u_i .$$

Note that $d\psi_i$ should not be so large that the linearity assumption is violated.

If this algorithm is used on a linear-quadratic problem with linear terminal constraints, the directions of search $\overline{p}_i$, $i = 0$, $n - 1$ will be conjugate and convergence would be obtained in a finite number of steps. For a nonlinear problem, however, the directions $\overline{p}_i$, $i = 0$, $n - 1$, will not be conjugate in general due to the addition of δu from Eq. (24) at each step. To bypass this difficulty, one may try to satisfy the terminal constraints first and then hold them constant using the gradient projection scheme. This method would work well if the constraints are linear, but if the constraints are highly nonlinear, m_i will have to be chosen small enough so that linearization holds. In such a case, it might be better to approach near the optimum using the penalty function method and then refine the solution using the gradient projection method. Typically, in most of the optimization problems, the step size a_i gets smaller and smaller as one approaches the optimum. So the linearization assumption would not be violated and the gradient projection method would generate conjugate directions near the minimum.

IV. In-Flight Constraints

There are three types of possible in-flight constraints which may be added to the problem statement in section III:

1. Control variable inequality constraints; $N(u, t) \le 0$.   (26)

2. Control and state variable inequality constraints or mixed constraints; $C(x, u, t) \le 0$.   (27)

3. State variable inequality constraints; $S(x, t) \le 0$.   (28)

We first describe general methods (a), (b) and (c) applicable to all of these cases. Then we describe special methods (d) and (e) for particular types of constraints.

a) Penalty Function Methods

Consider a scalar mixed constraint

$$c(x, u, t) \le 0 . \tag{29}$$

Introduce a new state variable r such that

$$\dot{r} = \begin{cases} Kc^2 & \text{if } c > 0 \\ 0 & \text{if } c \le 0 \end{cases} \tag{30}$$

where K is a large positive constant and

$$r(t_o) = 0 .$$

Then if $r(t_f) \cong 0$, the constraint $c \le 0$ is approximately satisfied.

The Interior Penalty Method of (8) tries to solve a sequence of minimization problems

$$P[u, r] = \phi(x(t_f), t_f) - r \int_{t_o}^{t_f} \frac{dt}{c(x, u, t)} \tag{31}$$

where r is a positive scalar and tends to zero. It can be shown that this method approaches the constraint boundaries from the interior (8).

Our experience has shown that these methods work poorly on highly nonlinear control problems. Lasdon et al. (8) encounter considerable difficulty in solving the re-entry problem. Moreover the constraint can never be exactly satisfied because these methods work by violation of the constraints.

b) <u>Transformation of Variables</u>

M. J. Box (15) has used this method for solving some nonlinear programming problems. It can be used for optimal control problems also, e.g., if a variable S has to be positive, we can use another variable y which is unconstrained and is related to S as

$$\text{(i)} \quad S = y^2 \tag{32}$$

or

$$\text{(ii)} \quad S = e^y \tag{33}$$

Similarly, if $0 \leqslant \colon \leqslant 1$

$$\text{(i)} \quad S = \sin^2 y \tag{34}$$

or

$$\text{(ii)} \quad S = \frac{e^y}{e^y + e^{-y}} \tag{35}$$

If $S_{min} \leqslant S \leqslant S_{max}$,

$$S = S_{min} + (S_{max} - S_{min})\sin^2 y \tag{36}$$

Then an unconstrained problem in y space is solved.

These methods are applicable to control and mixed type constraints only. Moreover, they produce slow convergence near the boundaries, e.g., if $S_{min} \leqslant S \leqslant S_{max}$ and the above transformation is used,

$$\frac{\partial S}{\partial y} = (S_{max} - S_{min})\sin 2y \tag{37}$$

which will be zero for

$$y = 0, \frac{\pi}{2} \quad \text{or for} \quad S = S_{min}, S_{max} \ .$$

c) <u>Gradient Projection Method</u>

Bryson, Denham, and Dreyfus (16) have shown that inequality constraints can be handled by solving for a set of inner-point equality constraints plus control constraints. Gradient projection can be used

with the conjugate gradient method to handle inner point constraints in the same way as the terminal constraints. The gradient vector g is computed using equations given by Bryson and Denham (9). The conjugate directions are generated separately for the paths before and after the inner-point constraint. The gradient on the arc before the inner-point constraint is projected on the intersection of two subspaces viz. those of the inner-point constraints and the terminal constraints whereas the gradient on the arc after the inner-point constraint is projected on one subspace only viz. subspace of the terminal constraints.

d) <u>Control Variable Inequality Constraints: Bang-Bang Solution</u>

If the control variable enters linearly in the equations of motion and in the performance index of the problem, one can show (13) that the control always lies on one of the boundaries. The problem is thus reduced to determining the switching times.

If $u_{min} \leqslant u \leqslant u_{max}$ and if t_i's are the switching times, then

$$\frac{\partial J}{\partial t_i} = (-1)^{i-1} (\lambda^T f_u)(u_{max} - u_{min}) \tag{38}$$

assuming at t_1, u goes from u_{max} to u_{min} (9).

Treating t_i as control parameters, we can iterate on them to obtain optimum switching times. If the number of switching times is unknown, it is better to start with more switching times than anticipated. The above technique can eliminate some switching times, but it cannot add extra switching times.

Then parameter optimization can be carried out using the conjugate gradient method (section IIa).

e) State Variable Inequality Constraints (SVIC); Separation of Arcs

This method is due to Speyer (17). It is applicable whenever the order of the SVIC is one less than the number of state variables in the system. In such cases, it becomes possible to compute the unconstrained arcs separately (10). One finds that the motion along the constraint boundary depends only on one state variable. Using this as the variable of integration, the value of the performance index along the constraint boundary is expressed as a function of the entry and exit point values of this variable. These functions are lumped suitably with objective functions along unconstrained arcs and the problem is reduced to a set of unconstrained problems. Speyer, Mehra and Bryson (10) use this method to solve the problem of range-maximization of a re-entry glider (9). The results obtained by them show that this method is very powerful, whenever it can be applied to problems with SVIC.

V. Flight Path For Minimum Time Climb-To-Cruise
of a V/STOL Aircraft

Compared to conventional aircraft, V/STOL aircraft have an extra control variable, namely the angle between the thrust direction and a reference axis in the aircraft. It is of interest to know how this extra control variable may be used to improve the performance of the aircraft.

If a flight is long enough, it can be divided into three paths:

(i) Climb phase starting from the ground and going up to some cruise condition;

(ii) Cruise at some constant altitude and velocity;

(iii) Landing phase.

-13-

Depending on the particular use to which the V/STOL aircraft is put, there may be flight path constraints on (i) and (iii).

If the cruise conditions are known, the optimization problem reduces to optimization of the two arcs (i) and (iii) separately, because the cruise conditions specify the state completely at the end of path (i) and at the beginning of path (iii).

Here, we shall consider the hypothetical jet-lift aircraft to Ref. (18).[*] Gallant (19) has considered a tilt-wing V/STOL aircraft and obtained minimum-direct-cost flight paths for a 50 mile flight starting from the end of the transition to the beginning of the retransition.

Problem Formulation

The aircraft will be approximated as a mass-point. Figure 1 shows the forces acting on the aircraft. Figure 2 shows the thrust force in greater detail. It is assumed that the jet inlets are always pointed in the direction of the relative wind velocity. This approximation is reasonable in view of the rough model assumed for the V/STOL aircraft and in view of the final results which show that the angle-of-attack is kept small during most of the flight.

The equations of motion are:

$$\dot{V} = \frac{T}{m} \cos(\alpha+i) - \frac{D}{m} - g \sin \gamma - \frac{M}{m} V[1 - \cos(\alpha+i)] \tag{39}$$

$$\dot{\gamma} = \frac{T}{mV} \sin(\alpha+i) + \frac{L}{mV} - \frac{g}{V} \cos \gamma + \frac{M}{m} \sin(\alpha+i) \tag{40}$$

$$\dot{h} = V \sin \gamma \tag{41}$$

$$\dot{x} = V \cos \gamma \tag{42}$$

FIGURE 1

D_m = Momentum Drag Along V-axis.

D'_m = Momentum Drag $\perp$ To V-axis.

RATE OF AIR FLOW = $\dot{M}$
EXIT VELOCITY OF GASES = V_e

FIGURE 2

Force along V axis = $F_V = \dot{M}V_e \cos(\alpha+i) - \dot{M}V$

Force $\perp$ to V direction = $F_\gamma = \dot{M}V_e \sin(\alpha+i)$

Thrust $T = \dot{M}V_e - \dot{M}V$ (Equal net force when $(\alpha+i) = 0$)

$\therefore$ $F_V = T \cos(\alpha+i) - \dot{M}V(1 - \cos(\alpha+i))$

$F_\gamma = T \sin(\alpha+i) + \dot{M}V \sin(\alpha+i)$

Where

$$\text{Lift} \qquad L = \frac{1}{2} \rho V^2 C_L S \qquad\qquad\qquad (43)$$

$$\text{Drag} \qquad D = \frac{1}{2} \rho V^2 C_D S \qquad\qquad\qquad (44)$$

$$C_L = C_{L_\alpha} \alpha \qquad\qquad\qquad (45)$$

$$C_D = C_{D_o} + C_{D_1} \alpha^2 \qquad\qquad\qquad (46)$$

$$\text{Air Density} \quad \rho = .0023769(1 - .6875 \times 10^{-5} h)^{4.2561} \qquad (47)$$

Equation (47) holds for $h \leqslant 36,000$ ft.

The characteristics of the hypothetical aircraft are

$$\text{Thrust} \quad T = T_o \left(1 - \frac{.55h}{30,000} \right) \quad \text{where h is in ft.}$$

$$\text{Mass} \quad m = \frac{56902}{32.2} \text{ slugs} \quad \text{(taken as constant during climb)}$$

$$\text{Wing Area} \quad S = 421 \text{ ft}^2$$

$$C_{D_o} = .027$$

$$C_{L_\alpha} = 5.73$$

$$C_{D_1} = \frac{C_{L_\alpha}^2}{\pi e AR} = \frac{(5.73)^2}{\pi \times .9 \times 6} = 1.93$$

$$\text{Rate of Air Flow} \quad \dot{M} = T_o / (65 \times 32.2) \text{ slugs/sec.}$$

$$\text{if } T_o \text{ is in lb.}$$

There are three control variables in the problem:

Magnitude of thrust vector (T_o), $(0 \leqslant T_o \leqslant T_{o_{max}})$;

Direction of thrust vector (i);

Angle of attack (α) or pitch angle (θ).

-16-

It is preferable to use θ instead of α as the control variable. The use of θ as the control variable adds extra damping terms into the equations of motion which help in convergence.

We shall obtain <u>minimum time paths</u> under the following assumptions:

1) <u>Thrust</u>, T_o, is kept constant at its maximum value. This is a reasonable assumption for the climb phase of the flight. In particular, we shall use $T_o = 1.25$ mg.

2) <u>Initial conditions</u> for the problem are

$$V(0) = 0 \quad , \quad h(0) = 0 \quad , \quad x(0) = 0$$

The $\dot{\gamma}$ equation has a singularity at $V = 0$. To integrate the equations of motion numerically, we must start with a finite V. The aircraft would attain this velocity after flying for some time, say t_1, in some particular manner. This part of the flight may be partially or completely determined by restrictions on the runway available for take-off, e.g., if the aircraft must take-off vertically, then $\gamma(t_1) = 90^o$ where t_1 will be some time either during or at the end of the vertical take-off period. We will now consider a few specific cases.

<u>Unconstrained Take-Off</u>. To get an idea as to what the aircraft should do if there were no constraints imposed on it due to the ground, we shall consider the case in which the aircraft can even go underground. While this case is unrealistic, it will provide useful information about the optimal paths with constraints. We do not know whether a V/STOL aircraft should take-off like a conventional aircraft (by first picking up speed along the runway) or whether it should take-off directly making some angle $\gamma(0+) > 0$

to the horizontal. If we solve the unconstrained problem treating $\gamma(t_1)$ as a control parameter, we should be able to answer this question.

The initial conditions for this case may, therefore, be taken as, (treating t_1 as starting time denoted by 0)

$V(0) = 50$ ft/sec

$\gamma(0)$ chosen to make $\lambda_\gamma(0) = 0$.

(This means that the optimization process must drive $\lambda_\gamma(0)$ to zero.)

$h(0) = 0$; $x(0) = 0$.

Changing $h(0)$ from 0 to several hundred feet will not change the results significantly.

The terminal conditions are the cruise conditions. The final time, t_f, is to be minimized:

$\gamma(t_f) = 0$

$h(t_f) = 20,000$ ft

$V(t_f)$ free

$x(t_f)$ free

A constraint on $V(t_f)$ could be met easily either by changing the path slightly or by changing thrust magnitude towards the end of the climb phase. The control variables used are θ and i.

Figures 3, 4, 5a, 6, 7, and 8 show the results obtained for the case when there are no constraints on take-off. The optimum value of $\gamma(0)$ at $V = 50$ ft/sec turns out to be about 7°. But the interesting fact is that γ soon becomes negative and the aircraft goes about 300 ft underground. Reasons for this seem to be:

-18-

FIG. 3 ALTITUDE VS. RANGE HISTORIES FOR (i) UNCONSTRAINED TAKE-OFF (ii) VERTICAL TAKE-OFF

FIG. 4 VELOCITY vs. RANGE FOR (i) UNCONSTRAINED TAKE-OFF (ii) VERTICAL TAKE-OFF

FIG. 5a FLIGHT-PATH ANGLE, γ, (a+i), AND THRUST DIRECTION, a+i+γ, VS. TIME FOR UNCONSTRAINED TAKE-OFF.

FIG. 5b FLIGHT-PATH ANGLE AND $(\alpha+i)$ VS. TIME WITH VERTICAL TAKE-OFF CONSTRAINT.

FIG. 6 PITCH ANGLE, θ, VS. TIME FOR (i) UNCONSTRAINED
TAKE-OFF (ii) VERTICAL TAKE-OFF.

FIG. 7 JET-TILT ANGLE, i, vs. TIME FOR (i) UNCONSTRAINED TAKE-OFF (ii) VERTICAL TAKE-OFF.

FIG. 8   ANGLE-OF-ATTACK VS. TIME FOR (i) UNCONSTRAINED TAKE-
OFF (ii) VERTICAL TAKE-OFF

(i) The thrust is greater at lower altitudes;

(ii) The aircraft should pick up velocity as fast as possible in order
to generate aerodynamic lift. Lift obtained from tilting the jet
is not very efficient because it gives lots of momentum drag.
The angle (a+i) is apparently kept low in order to keep this drag
low (cf. Fig. 5a).

To keep the surface drag low, angle of attack a is also kept
small as shown in Fig. 8. The aircraft dives down because gravity
helps it in picking up speed. Figure 4 shows velocity vs. range.

After the aircraft has picked up velocity during the diving
maneuver, γ increases quickly to a maximum value of 56.6° (Fig. 5a).
Figure 3 shows how h increases during this phase. However, θ also
increases at the same time so that $a = \theta - \gamma$ remains small. Jet-tilt
angle i is also kept small. Thus, the total drag is kept low. This
maneuver is followed by a rapid change in θ to a negative value of
about -25°. This is necessary to meet the terminal condition on γ
viz. $\gamma(t_f) = 0$. The total time taken by the aircraft is 53 sec. Calcu-
lations show that if the aircraft is made to climb vertically all the
way up from the ground, it takes twice as much time. The velocity
in that case never exceeds 300 ft/sec.

Thus the results show that a V/STOL aircraft without take-off
constraints should fly very much like a conventional aircraft. Aero-
dynamic lift is more efficient than jet-lift. On the other hand, the
aircraft should keep angle-of-attack a small to keep aerodynamic
drag low.

Horizontal Take-Off Constraint. Let us now impose the constraint
that the aircraft cannot go underground. However, it can still run
along the ground. Numerical results show that when the aircraft
reaches V $\approx$ 300 ft/sec, the optimal path no longer dives down. We
could integrate the equations of motion of the aircraft on the ground
to calculate the distance in which the aircraft can attain this velocity.
This also indicates that the best take-off for a STOL aircraft is to fly
parallel to the ground at low altitude for a considerable distance.

Vertical Take-Off Constraint. We now impose the restriction that
the aircraft must fly vertically up to an altitude of 1000 feet. From
the results obtained above, it appears that the best way to do this
would be to make $\theta = 90^\circ$ so that $a = 0$, $i = 0$, $\dot{\gamma} = 0$. Integration of
the $\dot{V}$ equation gives V = 125 ft/sec at h = 1000 ft. Time taken is 8
seconds. The optimization problem is now solved with the following
initial conditions:

$$V(8) = 125 \text{ ft/sec}$$
$$\gamma(8) = 90^\circ$$
$$h(8) = 1000 \text{ ft.}$$
$$x(8) = 0$$

The results are shown in Figs. 3, 4, 5b, 6, 7, and 8. The
total path (from take-off) is 60 seconds long and is similar to the
unconstrained take-off case. The aircraft goes up first due to posi-
tive γ, but soon dives down to a minimum altitude of about 980 ft.
The control variables θ and i have discontinuities at t = 8 sec. when
the constraints are relaxed.

Similar behavior would be obtained if the aircraft were con-
strained to take-off at some other constant value of flight path angle

γ_C. The equation $\dot{\gamma} = 0$ determines one of the control variables in terms of the other (say i in terms of θ). If θ is constrained by $\theta \leqslant \gamma_C$, as in the case above, one would intuitively expect that θ would remain constant at γ_C.

VI. Conclusion

Our computational experience has shown that the conjugate gradient method, though very efficient for simple optimization problems, may run into difficulties when applied to more complicated problems. Some of the difficulties that may be encountered are:

1. Gradient of the objective function with respect to the step size may not become zero or small enough during one-dimensional search. Accumulation of errors due to this source can produce directions of search which increase rather than decrease the performance index. In such cases, it was found useful to revert back to the local gradient direction and start the process over again. This procedure is similar to the one suggested by Beckman (20) and also used by Fletcher and Reeves (2) for nonlinear programming problems.

2. Use of penalty functions may split the "frozen-point" eigen-values of the linearized system far apart and make convergence extremely slow. The use of the gradient projection method, though more complicated, may help in this case, particularly near the optimum.

Conjugate Gradient Methods vs. Steepest Descent Methods:

(i) For optimal control problems having either no or few constraints, conjugate gradient methods, though requiring more programming, are faster and lead to a better solution than steepest descent methods. For linear-quadratic problems, conjugate gradient methods reach the optimum in a finite number of steps.

(ii) For optimal control problems with a large number of constraints, conjugate gradient methods run into the above-mentioned difficulties. It then becomes necessary to control the step size during the one-dimensional search and the directions of search are no longer conjugate to each other. In nonlinear problems with nonlinear constraints, it is not clear that conjugate gradient methods would do better than steepest descent methods except when starting close to the optimum.

Conjugate Gradient Methods vs. Second Variation Methods:

(i) Conjugate gradient methods require less programming and less computation per iteration than second variation methods.

(ii) Second variation methods require the matrix of second variations of the Hamiltonian with respect to the control (H_{uu}) to be non-singular. Conjugate gradient methods do not require this.

(iii) Conjugate gradient methods do not converge to extremals containing conjugate points, whereas second variation methods try to converge towards these extremals.

(iv) Second variation methods lead to more accurate solutions than conjugate gradient methods, particularly to better control histories.

References

1. Hestenes, M. R., and Stiefel, E. (1952) "Method of Conjugate Gradient for Solving Linear Systems," J. Res. N.B.S., Vol. 49, pp. 409.

2. Fletcher, R., and Reeves, C. M., "Function Minimization by Conjugate Gradients," Computer Journal, July 1964.

3. Hayes, R. M., "Iterative Methods of Solving Linear Problems on Hilbert Spaces," Nat. Bus. Stds., Applied Math Series 39 (1954).

4. Antosiewicz, H. A., and Rheinboldt, W. C., "Numerical Analysis and Functional Analysis" in Survey of Numerical Analysis (J. Todd, ed.), McGraw-Hill, 1962.

5. Daniel, J. W., "The Conjugate Gradient Method for Linear and Nonlinear Operator Equations," Siam J. Numer. Anal., Vol. 4, No. 1, 1967.

6. Lasdon, L. S., Mitter, S., Warren, A. D., "The Method of Conjugate Gradients for Optimal Control Problems," IEEE, Automatic Control, April 1967.

7. Sinnott, J. F., Luenberger, D. G., "Solution of Optimal Control Problems by the Method of Conjugate Gradients," JACC 1967, Preprints, pp. 566-575.

8. Lasdon, Warren, Rice, "An Interior Penalty Method for Inequality Constrained Optimal Control Problems," JACC 1967, Preprint, pp. 538-549.

9. Bryson, A. E., and Denham, W. F., "Optimal Programming Problems With Inequality Constraints II; Solution by Steepest Descent," AIAA Journal, Vol. 2, No. 1, January 1964.

10. Speyer, J., Mehra, R. K., and Bryson, A. E., "The Separate Computation of Arcs for Optimal Flight Paths With State Variable Inequality Constraints," May 1967, TR No. 526, Division of Engineering and Applied Physics, Harvard University, Cambridge, Massachusetts.

11. Rutishauser, H., "Theory of Gradient Methods," Chapter II in Stiefel E: "Über Einige Methoden der Relaxationrechnung," Z. Angnew, Math und Phy., 1952.

12. Moyer, H. G. and Pinkham, G., "Several Trajectory Optimization Techniques, Part II: Application" in "Computing Methods in Optimization Problems," Ed. Balakrishnan, A. V. and Neustadt, L. W., 1964, Academic Press.

13. Bryson, A. E. and Ho, Y. C., Lecture Notes, Division of Engineering and Applied Physics, Harvard University, Cambridge, Massachusetts, 1966-1967.

14. Rosen, J. B., "The Gradient Projection Method for Nonlinear Programming Part I: Linear Constraints," J. SIAM, Vol. 8, No. 1 (1960), pp. 181-217.

15. Box, M. J., "A Comparison of Several Optimization Methods and the Use of Transformations in Constrained Problems," British Computer Journal, 1966 Vol.

16. Bryson, A. E., Denham, W. F. and Dreyfus, S. E., "Optimal Programming Problems with Inequality Constraints. I. Necessary Conditions for Extremal Solutions," AIAA Journal, Vol. 1, pp. 2544-2550, November 1963.

17. Speyer, J. L., ")ptimization and Control of Nonlinear Systems with Inflight Constraints," Ph.D. Thesis, Chapters II and III, Harvard University, Cambridge, Massachusetts, to appear soon.

18. Miller, R. H. et al., "A Systems Analysis of Short Haul Air Transportation," Part III, TR-65-1 prepared for the U. S. Department of Commerce by the Flight Transportation Laboratory, Massachusetts Institute of Technology, Cambridge, Massachusetts, August 1965, pp. II-30.

19. Gallant, R. A., "Application of the Calculus of Variations in Determining Optimum Flight Profiles For Commercial Short Haul Aircraft," Master of Science Thesis, Massachusetts Institute of Technology, February 1967.

20. Beckman, F. S. (1960), "The Solution of Linear Equations by the Conjugate Gradient Method," in "Mathematical Methods for Digital Computers," Ralston, A. and Wilf, H. S. (Eds.), Vol. I, Wiley.

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)	2a. REPORT SECURITY CLASSIFICATION
Division of Engineering and Applied Physics Harvard University Cambridge, Massachusetts	Unclassified
	2b. GROUP

3. REPORT TITLE

CONJUGATE GRADIENT METHODS WITH AN APPLICATION TO V/STOL FLIGHT-PATH OPTIMIZATION

4. DESCRIPTIVE NOTES *(Type of report and inclusive dates)*

Interim technical report

5. AUTHOR(S) *(First name, middle initial, last name)*

R. K. Mehra and A. E. Bryson, Jr.

6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
November 1967	36	20

8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)
N00014-67-A-0298-0006 and b. PROJECT NO. NASA NGR-22-007-068	Technical Report No. 543
c.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)
d.	

10. DISTRIBUTION STATEMENT

Reproduction in whole or in part is permitted for any purpose of the United States Government.

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY
	Office of Naval Research

13. ABSTRACT

Conjugate gradient methods have recently been applied to some simple optimization problems and have been shown to converge faster than the methods of steepest descent. The present paper considers application of these methods to more complicated problems involving terminal as well as in-flight constraints. A number of methods are suggested to handle these constraints and the numerical difficulties associated with each method are discussed. The problem of flight-path optimization of a V/STOL aircraft has been considered and minimum time paths for the climb phase have been obtained using the conjugate gradient algorithm. In conclusion, some remarks are made about the relative efficiency of the different optimization schemes presently available for the solution of optimal control problems.

DD FORM 1473 (PAGE 1)
1 NOV 65
S/N 0101-807-6811

Unclassified
Security Classification
A-31408

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Optimization						
Conjugate						
Gradient						

Academy Library (DFSLB)
U. S. Air Force Academy
Colorado Springs, Colorado 80912

AEDC (ARO, INC)
Attn: Library/Documents
Arnold AFB, Tenn. 37389

Aeronautics Library
Graduate Aeronautical Laboratories
California Institute of Technology
1201 E. California Blvd.
Pasadena, California 91109

Aerospace Corporation
P. O. Box 95085
Los Angeles, Calif. 90045
Attn: Library Acquisitions Group

Airborne Instruments Laboratory
Deerpark, New York 11729

AFAL (AVTE/R. D. Larson)
Wright-Patterson AFB
Ohio 45433

AFCRL (CRMXLR)
ARCRL Research Library, Stop 29
L. G. Hanscom Field
Bedford, Mass. 01731

AFETR (ETLIG - 1)
STINFO Officer (for library)
Patrick AFB, Florida 32925

AFETR Technical Library
(ETV, MU-135)
Patrick AFB, Florida 32925

AFFTC (FRBPP-2)
Technical Library
Edwards AFB, Calif. 93523

APGC (PHBPS-12)
Eglin AFB
Florida 32542

ARL (ARIY)
Wright-Patterson AFB
Ohio 45433

AUL3T-9663
Maxwell AFB
Alabama 36112

Mr. Henry L. Bachman
Assistant Chief Engineer
Wheeler Laboratories
122 Cuttermill Road
Great Neck, N. Y. 11021

Bendix Pacific Division
11600 Sherman Way
North Hollywood, Calif. 91605

Colonel A. D. Blue
RTD (RTTL)
Bolling AFB
Washington, D. C. 20332

California Institute of Technology
Pasadena, California 91109
Attn: Documents Library

Carnegie Institute of Technology
Electrical Engineering Dept.
Pittsburg, Pa. 15213

Central Intelligence Agency
Attn: OCR/DD Publications
Washington, D. C. 20505

Chief of Naval Operations
OP-07
Washington, D. C. 20350 [2]

Chief of Naval Research
Department of the Navy
Washington, D. C. 20360
Attn: Code 427 [3]

Commandant
U. S. Army and General Staff College
Attn: Secretary
Fort Leavenworth, Kansas 66370

Commander
Naval Air Development and
Material Center
Johnsville, Pennsylvania 18974

Commanding General
Frankford Arsenal
Attn: SMUFA-L6000 (Dr. Sidney Ross)
Philadelphia, Pa. 19137

Commandant
U. S. Army Air Defense School
Attn: Missile Sciences Div. C and S Dept.
P. O. Box 9390
Fort Bliss, Texas 79916

Commander
U. S. Naval Air Missile Test Center
Point Mugu, California 93041

Commanding General
Attn: STEWS-WS-VT
White Sands Missile Range
New Mexico 88002 [2]

Commanding General
U. S. Army Electronics Command
Fort Monmouth, N. J. 07703
Attn: AMSEL-SC
RD-D
RD-G
RD-GF
RD-MAT
XL-D
XL-E
XL-C
XL-S
HL-D
HL-CT-R
HL-CT-P
HL-CT-L
HL-CT-O
HL-CT-I
HL-CT-A
NL-D
NL-A
NL-P
NL-R
NL-S
KL-D
KL-E
KL-S
KL-T
VL-D
WL-D

Commanding General
U. S. Army Material Command
Attn: AMCRD-RS-DE-E
Washington, D. C. 20315

Commanding General
U. S. Army Missile Command
Attn: Technical Library
Redstone Arsenal, Alabama 35809

Commanding Officer
Naval Avionics Facility
Indianapolis, Indiana 46241

Commanding Officer
U. S. Army Limited War Laboratory
Attn: Technical Director
Aberdeen Proving Ground
Aberdeen, Maryland 21005

Commanding Officer
U. S. Army Materials Research Agency
Watertown Arsenal
Watertown, Massachusetts 02172

Commanding Officer
U. S. Army Security Agency
Arlington Hall
Arlington, Virginia 22212

Commanding Officer and Director
U. S. Naval Underwater Sound Lab.
Fort Trumbull
New London, Conn. 06840

Defense Documentation Center
Attn: TISIA
Cameron Station, Bldg. 5
Alexandria, Virginia 22314 [20]

Det No. 6, OAR (LODAR)
Air Force Unit Post Office
Los Angeles, Calif. 90045

Director
Advanced Research Projects Agency
Department of Defense
Washington, D. C. 20301

Director for Materials Sciences
Advanced Research Projects Agency
Department of Defense
Washington, D. C. 20301

Director
Columbia Radiation Laboratory
Columbia University
538 West 120th Street
New York, New York 10027

Director
Coordinated Science Laboratory
University of Illinois
Urbana, Illinois 61803

Director
Electronics Research Laboratory
University of California
Berkeley, California 94720

Director
Electronic Sciences Laboratory
University of Southern California
Los Angeles, California 90007

Director
Microwave Laboratory
Stanford University
Stanford, California 94305

Director - Inst. for Exploratory
Research
U. S. Army Electronics Command
Attn: Mr. Robert O. Parker
Executive Secretary, JSTAC
(AMSEL-XL-D)
Fort Monmouth, N. J. 07703

Director
National Security Agency
Fort George G. Meade
Maryland 20755
Attn: James T. Tippett

Director, Naval Research Laboratory
Technical Information Officer
Washington, D. C.
Attn: Code 2000 [8]

Director
Research Laboratory of Electronics
Massachusetts Institute of Technology
Cambridge, Mass. 02139

Director
Stanford Electronics Laboratories
Stanford University
Stanford, California 94305

Commanding Officer
Naval Ordnance Laboratory
Corona, California 91720

Commanding Officer
Naval Ordnance Laboratory
White Oak, Maryland 21502 [2]

Commanding Officer
Naval Ordnance Test Station
China Lake, Calif. 93555

Commanding Officer
Naval Training Device Center
Orlando, Florida 32811

Commanding Officer
Office of Naval Research Branch Office
1030 East Green Street
Pasadena, California

Commanding Officer
Office of Naval Research Branch Office
219 South Dearborn Street
Chicago, Illinois 60604

Commanding Officer
Office of Naval Research Branch Office
495 Summer Street
Boston, Massachusetts 02210

Commanding Officer
Office of Naval Research Branch Office
207 West 24th Street
New York, New York 10011

Commanding Officer
Office of Naval Research Branch Office
Box 39, Fleet Post Office
New York 09510 [2]

Commanding Officer
U. S. Army Electronics R & D Activity
White Sands Missile Range
New Mexico 88002

Commanding Officer
U. S. Army Engineer R & D Laboratory
Attn: STINFO Branch
Fort Belvoir, Virginia 22060

Commanding Officer
U. S. Army Research Office (Durham)
Attn: CRD-AA-IP (Richard O. Ulsh)
Box CM, Duke Station
Durham, North Carolina 27706

Commanding General
USASTRATCOM
Technical Information Center
Fort Huachuca, Arizona 85613

Commanding Officer
Harry Diamond
Attn: Dr. Berthold Altman (AMXDO-TI)
Connecticut Ave. & Van Ness St. NW
Washington, D. C. 20438

Commanding Officer
Human Engineering Laboratories
Aberdeen Proving Ground
Maryland 21005

Commanding Officer
U. S. Army Ballistics Research Lab.
Attn: V. W. Richards
Aberdeen Proving Ground
Maryland 21005

Director, USAF Project RAND
Via: Air Force Liaison Office
The RAND Corporation
1700 Main Street
Santa Monica, Calif. 90406
Attn: Library

Director
U. S. Army Engineer Geodesy,
Intelligence and Mapping
Research and Development Agency
Fort Belvoir, Virginia 22060

Director
U. S. Naval Observatory
Washington, D. C. 20390

Director, U. S. Naval Security Group
Attn: G43
3801 Nebraska Avenue
Washington, D. C. 20390

Division of Engineering and Applied
Physics
130 Pierce Hall
Harvard University
Cambridge, Massachusetts 02138

Professor A. A. Dougal, Director
Laboratories for Electronics and
Related Sciences Research
University of Texas
Austin, Texas 78712

ESD (ESTI)
L. G. Hanscom Field
Bedford, Mass. 01731 [2]

European Office of Aerospace Research
Shell Building
47 Rue Cantersteen
Brussels, Belgium [2]

Colonel Robert E. Fontana
Dept. of Electrical Engineering
Air Force Institute of Technology
Wright-Patterson AFB, Ohio 45433

General Electric Company
Research Laboratories
Schenectady, New York 12301

Professor Nicholas George
California Institute of Technology
Pasadena, California 91109

Goddard Space Flight Center
National Aeronautics and Space Admin.
Attn: Library, Documents Section
Code 252
Green Belt, Maryland 20771

Dr. John C. Hancock, Director
Electronic Systems Research Laboratory
Purdue University
Lafayette, Indiana 47907

Dr. H. Harrison, Code RRE
Chief, Electrophysics Branch
National Aeronautics and Space Admin.
Washington, D. C. 20546

Head, Technical Division
U. S. Naval Counter Intelligence
Support Center
Fairmont Building
4420 North Fairfax Drive
Arlington, Virginia 22203

Headquarters
Defense Communications Agency
The Pentagon
Washington, D. C. 20305

Dr. L. M. Hollinsworth
ARCRL (CRN)
L. G. Hanscom Field
Bedford, Massachusetts 01731

Hunt Library
Carnegie Institute of Technology
Schenley Park
Pittsburgh, Pa. 15213

The Johns Hopkins University
Applied Physics Laboratory
8621 Georgia Avenue
Silver Spring, Maryland 20910
Attn: Boris W. Kuvshinoff
Document Librarian

Lt. Col. Robert B. Kalisch
Chief, Electronics Division
Directorate of Engineering Sciences
Air Force Office of Scientific Research
Arlington, Virginia 22209 [5]

Colonel Kee
ARFSTE
Hqs. USAF
Room ID-429, The Pentagon
Washington, D. C. 20330

Dr. S. Benedict Levin, Director
Institute for Exploratory Research
U. S. Army Electronics Command
Fort Monmouth, New Jersey 07703

Los Alamos Scientific Laboratory
Attn: Reports Library
P. O. Box 1663
Los Alamos, New Mexico 87544

Librarian
U. S. Naval Electronics Laboratory
San Diego, California 95152 [2]

Lockheed Aircraft Corp.
P. O. Box 504
Sunnyvale, California 94088

Dr. I. R. Mirman
AFSC (SCT)
Andrews Air Force Base, Maryland

Lt. Col. Bernard S. Morgan
Frank J. Seiler Research Laboratory
U. S. Air Force Academy
Colorado Springs, Colorado 80912

Dr. G. J. Murphy
The Technological Institute
Northwestern University
Evanston, Illinois 60201

Mr. Peter Murray
Air Force Avionics Laboratory
Wright-Patterson AFB, Ohio 45433

NASA Lewis Research Center
Attn: Library
21000 Brookpark Road
Cleveland, Ohio 44135

NASA Scientific & Technical
Information Facility
Attn: Acquisitions Branch (S/AK/DL)
P. O. Box 33
College Park, Maryland 20740 [2]

National Science Foundation
Attn: Dr. John R. Lehmann
Division of Engineering
1800 G Street, NW
Washington, D. C. 20550

National Security Agency
Attn: R4 - James Tippet
Office of Research
Fort George C. Meade, Maryland 20755

Naval Air Systems Command
AIR 03
Washington, D. C. 20360 [2]

Naval Electronics Systems Command
ELFX 03
Falls Church, Virginia 22046 [2]

Naval Ordnance Systems Command
ORD 32
Washington, D. C. 20360 [2]

Naval Ordnance Systems Command
SHIP 035
Washington, D. C. 20360

Naval Ship Systems Command
SHIP 031
Washington, D. C. 20360

New York University
College of Engineering
New York, New York 10019

Dr. H. V. Noble
Air Force Avionics Laboratory
Wright-Patterson AFB, Ohio 45433

Office of Deputy Director
(Research and Information Rm. 3D1037)
Department of Defense
The Pentagon
Washington, D. C. 20301

Polytechnic Institute of Brooklyn
55 Johnson Street
Brooklyn, New York 11201
Attn: Mr. Jerome Fox
Research Coordination

RAD (EMLAL-1)
Griffiss AFB, New York 13442
Attn: Documents Library

Raytheon Company
Bedford, Mass. 01730
Attn: Librarian

Lt. Col. J. L. Reeves
AFSC (SCBB)
Andrews Air Force Base, Md. 20331

Dr. A. A. Dougal
Asst. Director of Research
Office of Defense Res. and Eng.
Department of Defense
Washington, D. C. 20301

Research Plans Office
U. S. Army Research Office
3045 Columbia Pike
Arlington, Virginia 22204

Dr. H. Robl, Deputy Chief Scientist
U. S. Army Research Office (Durham)
Durham, North Carolina 27706

Emil Schafer, Head
Electronics Properties Info. Center
Hughes Aircraft Company
Culver City, California 90230

School of Engineering Sciences
Arizona State University
Tempe, Arizona 85281

SAMSO (SMSDI-STINFO)
AF Unit Post Office
Los Angeles, California 90045

SSD (SSTRT/Lt. Starbuck)
AFUPO
Los Angeles, California 90045

Superintendent
U. S. Army Military Academy
West Point, New York 10996

Colonel A. Swan
Aerospace Medical Division
AMD (AMRXI)
Brooks AFB, Texas 78235

Syracuse University
Dept. of Electrical Engineering
Syracuse, New York 13210

University of California
Santa Barbara, California 93106
Attn: Library

University of Calif. at Los Angeles
Dept. of Engineering
Los Angeles, California 90024

University of Michigan
Electrical Engineering Dept.
Ann Arbor, Michigan 48104

U. S. Army Munitions Command
Attn: Technical Information Branch
Picatinny Arsenal
Dover, New Jersey 07801

U. S. Army Research Office
Attn: Physical Sciences Division
3045 Columbia Pike
Arlington, Virginia 22204

U. S. Atomic Energy Commission
Division of Technical Information Ext.
P. O. Box 62
Oak Ridge, Tenn. 37831

Dept. of Electrical Engineering
Texas Technological College
Lubbock, Texas 79409

U. S. Naval Weapons Laboratory
Dahlgren, Virginia 22448

Major Charles Weepy
Technical Division
Deputy for Technology
Space Systems Division, AFSC
Los Angeles, California 90045

The Walter Reed Institute of Research
Walter Reed Medical Center
Washington, D. C. 20012

AFSC (SCTR)
Andrews Air Force Base
Maryland 20331

Weapons Systems Test Division
Naval Air Test Center
Patuxent River, Maryland 20670
Attn: Library

Weapons Systems Evaluation Group
Attn: Col. Daniel W. McElwee
Department of Defense
Washington, D. C. 20305

Yale University
Engineering Department
New Haven, Connecticut 06720

Mr. Charles F. Yost
Special Asst. to the Director of Research
NASA
Washington, D. C. 20546

Dr. Leo Young
Stanford Research Institute
Menlo Park, California 94025